

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 14, 15 AND 22,

IN

TOWNSHIP 13 NORTH, RANGE 7 EAST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Ronald K. Baugh
Supervisory Cadastral Surveyor

Under special instructions dated **and** approved **July 23, 2007**, which
provided for the surveys included under Group Number **1038**, and
assignment instructions dated **July 23, 2007**,

Survey commenced **July 24, 2007**
Survey completed **August 14, 2007**

INDEX DIAGRAM

Township 13 North, Range 7 East

6	5	4	3	2	1
7	8	9	10 14	11 8	12
18	17	16 12	15 7 11	14 4 7	13
19	20	21 10	22 6 9	23 3 4	24
30	29	28	27	26	25
31	32	33	34	35	36

The Subdivision of Section 14.....Page 14
The Subdivision of Section 15.....Page 16
The Subdivision of Section 22.....Page 19

T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, and the subdivision of sections 14, 15, and 22, T. 13 N., R. 7 E., Salt Lake Meridian, Utah.

History of Surveys

	Surveyed by	Retr. or Resurveyed by
SOUTH BOUNDARY		
All	J. Bausman	1869
EAST BOUNDARY		
All	F. Dickert	1870
All		A.P. Hanson 1896
WEST BOUNDARY		
All	T.C. Bailey & J.G. Burrill	1875
NORTH BOUNDARY		
All	T.C. Bailey & J.G. Burrill	1875
SUBDIVISION AND MEANDERS		
All	T.C. Bailey & J.G. Burrill	1875

T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

This survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1038 dated July 23, 2007.

The direction of the lines was determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) methods throughout the survey. The positional accuracy of this survey complies with the *Standards and Guidelines for Cadastral Surveys Using GPS Methods*, dated May 9, 2001, Version 1.0. Trimble model 5800 GPS receivers were used for field collection. Cadastral Measurement Management (CMM) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Cadastral Control Network was derived from GPS static observations, post processed by the National Geodetic Survey, Online Positioning User Service(OPUS), utilizing Continuously Operating Reference Stations (CORS); CNRSPRNGD_UT2004, MONSANTO-SODA and AUBURN HATCHERY.

The geographic position of the corner of sections 23, 24, 25 and 26, as determined by direct RTK methods from the National Geodetic Survey OPUS solution is as follows:

Latitude: 41°50'45.255" N. Longitude: 111°06'33.715" W.
NAD 1983, N.A.V.D. 1988 Elev. 6579 ft.
Network Accuracy = 0.200 meter at 95% confidence.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 N., R. 7 E., Salt Lake Meridian, Utah.

Reestablishment of the Survey executed by T.C. Bailey and J.G. Burrill in 1875.

Beginning at the corner of sections 23, 24, 25 and 26,
monumented with a sandstone, 30x18x5 inches firmly set and
dimly marked, 1 notch on the E and 2 notches on the S edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
22 inches in the ground to bedrock, with a magnet at base, and
in a mound of stone, 3 ft. base to top of aluminum cap marked:

T13N R7E
S23 S24
S26 S25
2007

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located in a wash that drains SW.

N. 0° 05.6' E., between sections 23 and 24.

41.252 Point for the 1/4 section corner of sections 23 and 24, at
proportionate distance, there is no remaining evidence of the
original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
24 inches in the ground, with a magnet at base, with aluminum
cap marked:

T13N R7E
1/4
S23 S24
2007

Set a steel fence post alongside the aluminum post.

The corner is located near the top of a ridge bearing N and S.

82.504 The corner of sections 13, 14, 23 and 24, monumented with a
sandstone, 15x10x5 inches, firmly set and plainly marked, 1
notches on the E and 3 notch on the S edges.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
24 inches in the ground, with a magnet at base, with aluminum
cap marked:

T13N	R7E
S14	S13
S23	S24

2007

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 06.8' E., between sections 13 and 14.

20.505 Point for the S 1/16 section corner of sections 13 and 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
24 inches in the ground, with a magnet at base, with aluminum
cap marked:

T13N	R7E
S	1/16
S14	S13

2007

Set a steel fence post alongside the aluminum post.

Corner of fences, bears S 9 ft. distance, fences extend W and
NE.

41.010 The 1/4 section corner of sections 13 and 14, monumented with
a sandstone, 15x8x4 inches, firmly set and plainly marked, 1/4
on W face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
20 inches in the ground to bedrock, with a magnet at base, and
in a mound of stone, 3 ft. base to top of aluminum cap marked:

T13N	R7E
1/4	
S14	S13

2007

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 23, 24, 25 and 26.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 88° 24.1'W., between sections 23 and 26.

- 39.121** The 1/4 section corner of sections 23 and 26, monumented with a sandstone, 16x10x8 inches, firmly set and plainly marked 1/4 on N face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground to bedrock, with a magnet at base, and in a collar of stone, with aluminum cap marked:

T13N R7E
S23
1/4 ———
S26
2007

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

S. 89° 13.5' W., beginning new measurement.

- 20.003** Point for the W 1/16 section corner of sections 23 and 26.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E
S23
W 1/16 ———
S26
2007

Set a steel fence post alongside the aluminum post.

- 40.006** The corner of sections 22, 23, 26 and 27, monumented with a sandstone, 12x12x10, inches, firmly set and plainly marked 2 notches on the S and E edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E
S22|S23
S27|S26
2007

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 16.3' W., between sections 22 and 23.

10.238 Point for the S-S 1/64 section corner of sections 22 and 23.
Not monumented.

20.476 Point for the S 1/16 section corner of sections 22 and 23. Not
monumented.

40.952 The 1/4 section corner of sections 22 and 23, monumented with
a sandstone, 15x12x10 inches, firmly set and plainly marked
1/4 on W face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
20 inches in the ground, to bedrock, with a magnet at base,
with aluminum cap marked:

T13N R7E
1/4
S22|S23
2007

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 27.4' W., beginning new measurement.

41.194 The corner of sections 14, 15, 22 and 23, monumented with a
boulder, 12x10x10 inches, firmly set and plainly marked 2
notches on the E and 3 notches on the S edges.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
26 inches in the ground, with a magnet at base, with aluminum
cap marked:

T13N R7E
S15|S14
S22|S23
2007

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Raise a mound of stone 4 ft. base, 2 ft. high, W of the
aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Falls in an E-W fence line.

From the corner of sections 13, 14, 23 and 24.

S. 89° 50.2' W., between sections 14 and 23.

39.094 The 1/4 section corner of sections 14 and 23, monumented with a sandstone, 15x7x3 inches, firmly set and plainly marked, 1/4 on NE face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E
S14
1/4 ———
S23
2007

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner of fences, bears SW 6 inches distance, fences extend N and W.

N. 89° 34.0' W., beginning new measurement.

39.999 The corner of sections 14, 15, 22 and 23.

N. 0° 05.0' E., between sections 14 and 15.

20.456 Point for the S 1/16 section corner of sections 14 and 15. Not monumented.

40.912 The 1/4 section corner of sections 14 and 15, monumented with a boulder, 16x10x4 inches, firmly set and plainly marked, 1/4 on W face.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E
1/4
S15|S14
2007

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 05.3' E., beginning new measurement.

20.661 Point for the N 1/16 section corner of sections 14 and 15, not monumented.

41.322 The corner of sections 10, 11, 14 and 15, monumented with a sandstone, 12x10x5 inches, firmly set and plainly marked, 2 notches on the E and 4 notches on the S edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground to bedrock, with a magnet at base, with aluminum cap marked:

T13N R7E	
S10	S11
<hr/>	
S15	S14
2007	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located in an E-W fence line.

From the 1/4 section corner of sections 11 and 14, monumented with a sandstone 12x10x3 inches, firmly set and plainly marked, 1/4 on the N face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground, to bedrock, with a magnet at base, with aluminum cap marked:

T13N R7E	
S11	
1/4	<hr/>
S14	
2007	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 89° 32.7' W., between sections 11 and 14.

20.233 Point for the W 1/16 section corner of sections 11 and 14.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
24 inches in the ground, with a magnet at base, with aluminum
cap marked:

T13N R7E
S11
W 1/16
S14
2007

Set a steel fence post alongside the aluminum post.

Corner of fences bears E 5 1/2 ft. distance, fences extend S
and W.

40.466 The corner of sections 10, 11, 14 and 15

From the corner of sections 22, 23, 26 and 27.

N. 89° 36.3' W., between sections 22 and 27.

10.136 Point for the E-E 1/64 section corner of sections 22 and 27.
Not monumented.

12.670 Point for the E-W-E-E 1/1024 section corner of sections 22 and
27. Not monumented.

15.204 Point for the W-E-E 1/256 section corner of sections 22 and
27. Not monumented.

20.272 Point for the E 1/16 section corner of sections 22 and 27. Not
monumented.

40.544 Point for the 1/4 section corner of sections 22 and 27, at
proportionate distance; there is no remaining evidence of the
original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
30 inches in the ground, with a magnet at base, with aluminum
cap marked:

T13N R7E
S22
1/4
S27
2007

Set a steel fence post alongside the aluminum post.

Corner falls on the south edge of a pasture.

60.816 Point for the W 1/16 section corner of sections 22 and 27. Not
monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

81.088

The corner of sections 21, 22, 27 and 28, monumented with a sandstone, 12x10x3 inches, firmly set and plainly marked, 3 notches on the E and 2 notches on the S edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E	
S21	S22
S28	S27
2007	

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the aluminum post.

N. 0° 19.7' E., between sections 21 and 22.

20.721

Point for the S 1/16 section corner of sections 21 and 22. Not monumented.

41.442

The 1/4 section corner of sections 21 and 22, monumented with a sandstone, 12x12x3 inches, firmly set and plainly marked, 1/4 on W face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E	
1/4	
S21	S22
2007	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 1 ft. high, W of the aluminum post.

N. 0° 20.4' E., beginning new measurement.

41.430

The corner of sections 15, 16, 21 and 22, monumented with a sandstone, 16x12x6 inches, firmly set and plainly marked, 3 notches on the E and S edges.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
24 inches in the ground, with a magnet at base, with aluminum
cap marked:

T13N R7E
S16 S15
S21 S22
2007

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 14, 15, 22 and 23.

N. 89° 05.3' W., between sections 15 and 22.

20.180 Point for the E 1/16 section corner of sections 15 and 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
24 inches in the ground, with a magnet at base, with aluminum
cap marked:

T13N R7E
S15
E 1/16 ———
S22
2007

Set a steel fence post alongside the aluminum post.

Corner of fences, bears S. 81° 55' E., 10.1 ft. distance,
fences extend N, S and E.

40.360 Point for the 1/4 section corner of sections 15 and 22, at
proportionate distance; there is no remaining evidence of the
original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
26 inches in the ground, with a magnet at base, with aluminum
cap marked:

T13N R7E
S15
1/4 ———
S22
2007

Set a steel fence post alongside the aluminum post.

60.540 Point for the W 1/16 section corner of sections 15 and 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
20 inches in the ground to bedrock, with a magnet at base, and
in a mound of stone, 3 ft. base to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T13N R7E
S15
W 1/16
S22
2007

Set a steel fence post alongside the aluminum post.

80.720 The corner of sections corner 15, 16, 21 and 22.

N. 0° 25.6' E., between sections 15 and 16.

41.190 The 1/4 section corner of sections 15 and 16, monumented with a sandstone, 16x12x8 inches, firmly set and plainly marked, 1/4 on W face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E
1/4
S16|S15
2007

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Raise a mound of stone 3 ft. base, 1 ft. high west of the aluminum post.

N. 0° 44.9' W., beginning new measurement.

20.469 Point for the N 1/16 section corner of sections 15 and 16.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E
N 1/16
S16|S15
2007

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 1 ft. high, W of aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.938

The corner of sections 9, 10, 15 and 16, monumented with a sandstone, 20x8x6 inches, firmly set and plainly marked 3 notches on the E and 4 notches on the S edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E	
S9	S10
S16	S15
2007	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From this corner, the corner of sections 3, 4, 33 and 34, on the north boundary of the township, bears N. 0° 51.1' E., 157.603 chains distance, monumented with a sandstone, 16x15x5 inches, firmly set, and plainly marked 3 notches on the E and W edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T14N R7E	
S33	S34
S4	S3
T13N R7E	
2007	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From this same corner, the corner of sections 8, 9, 16 and 17, bears S. 89° 21.0' W., 77.672 chains distance, monumented with a sandstone 16x10x6 inches, firmly set and plainly marked 4 notches on the E and S edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T13N R7E
 $\frac{S8|S9}{S17|S16}$
 2007

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 10, 11, 14 and 15.

N. 89° 09.5' W., between sections 10 and 15.

- 40.566** The 1/4 section corner of sections 10 and 15, monumented with a mound of stone in a N-S fence line. The original marked stone was not found. This position is harmoniously related to existing original corners, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and in a collar of stone, with aluminum cap marked:

T13N R7E
 S10
 1/4 ———
 S15
 2007

Set a steel fence post alongside the aluminum post.

Corner falls in a N-S fence line.

N. 89° 10.9' W., beginning new measurement.

- 20.179** point for the W 1/16 section corner of sections 10 and 15. Not monumented.

- 40.358** The corner of sections 9, 10, 15 and 16.
-

The Subdivision of Section 14
 T. 13 S., R. 7 E., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 14 and 23.

N. 0° 19.7' E., on the N - S centerline of section 14.

- 20.584** Point for the center S 1/16 section corner of section 14.

THE SUBDIVISION OF SECTION 14
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E
C
S1/16 | S14
C
2007

Set a steel fence post alongside the aluminum post.

Corner of fences bears E 2 ft. distance, fences extend N, S and E.

41.168 Point for the center 1/4 section corner of section 14, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E
C 1/4 S14
2007

Set a steel fence post alongside the aluminum post.

Corner is located 1 ft. W of a N-S fence line.

61.693 Point for the C-N 1/16 section corner of section 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E
C
N 1/16 | S14
C
2007

Set a steel fence post alongside the aluminum post.

Corner is located in a N-S fence line, 37 ft. south of corner of fences extending W and S.

82.218 The 1/4 section corner of sections 11 and 14.

From the 1/4 section corner of sections 13 and 14.

N. 89° 55.9' W., on the E - W centerline of section 14.

38.934 The center 1/4 section corner of section 14.

THE SUBDIVISION OF SECTION 14
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

59.019 Point for the center W 1/16 section corner of section 14. Not monumented.

79.104 The 1/4 section corner of sections 14 and 15.

From the S 1/16 section corner of section 13 and 14.

S. 89° 57.1' W., on the E - W centerline of the SE 1/4 of section 14.

39.014 The center S 1/16 section corner, of section 14.

From the point for the center W 1/16 section corner of sections 14.

N. 0° 07.2' E., on the N - S centerline of the NW 1/4 of section 14.

20.593 Point for the NW 1/16 section corner of section 14, at intersection with the E - W centerline of the NW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E
NW 1/16
S14
2007

Set a steel fence post alongside the aluminum post.

Corner of fences bears N 42 ft. distance, fences extend N and E.

41.186 The W 1/16 section corner of sections 11 and 14.

From the center N 1/16 section corner of section 14.

N. 89° 44.3' W., on the E - W centerline of the NW 1/4 of section 14.

20.159 The NW 1/16 section corner of section 14.

40.318 The point for the N 1/16 section corner of sections 14 and 15.

The Subdivision of Section 15
T. 13 N., R. 7 E., Salt Lake Meridian, Utah.

THE SUBDIVISION OF SECTION 15
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 15 and 22.

N. 0° 09.2' W., on the N - S centerline of section 15.

20.528 Point for the center S 1/16 section corner of section 15. Not monumented.

25.660 Point for the C-S-N-S 1/256 section corner of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

S15
C-S-N-S
1/256
2007

Set a steel fence post alongside the aluminum post.

41.056 Point for the center 1/4 section corner, at intersection with the E - W centerline of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T13S R7E
C 1/4
S15
2007

Set a steel fence post alongside the aluminum post.

61.622 Point for the center N 1/16 section corner of section 15. Not monumented.

82.188 The 1/4 section corner of sections 10 and 15.

From the 1/4 section corner of sections 14 and 15.

N. 88° 53.3' W., on the E - W centerline of section 15.

20.264 Point for the center E 1/16 section corner of section 15. Not monumented.

40.528 The center 1/4 section corner of section 15.

52.140 Fence line extends N and S.

60.499 Point for the center W 1/16 section corner of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

THE SUBDIVISION OF SECTION 15
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T13N R7E
W 1/16
C ——— C
S15
2007

Set a steel fence post alongside the aluminum post.

80.470 The 1/4 section corner of sections 15 and 16.

From the E 1/16 section corner of sections 15 and 22.

N. 0° 02.1' W., on the N - S centerline of the SE 1/4 of section 15.

20.492 Point for the SE 1/16 section corner, at intersection with the E - W centerline of the SE 1/4 of section 15. Not monumented.

25.615 Point for the C-S-N-SE 1/256 section corner of section 15.

Set a 5/8 inch rebar, 18 inches long, 10 inches below ground with a 3 inch diameter aluminum cap marked:

S15
C-S-N-SE
1/256
2007

Set a steel fence post 23 ft. west of rebar on line.

Corner falls in gravel road.

40.984 The point for the center E 1/16 section corner of section 15.

From the point for the S 1/16 section corner of sections 14 and 15.

N. 88° 59.3' W., on the E - W centerline of the SE 1/4 of section 15.

20.222 The point for the SE 1/16 section corner of section 15.

40.444 The point for the center S 1/16 section corner of section 15.

From the C-S-N-SE 1/256 section corner of section 15.

N. 88° 57.8' W., on the E - W centerline of the south 1/2 of the NW 1/4 of the SE 1/4 of section 15.

20.232 The C-S-N-S 1/256 section corner of section 15.

THE SUBDIVISION OF SECTION 15
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the W 1/16 section corner of sections 15 and 22.

N. 0° 08.2' E., on the N - S centerline of the SW 1/4 of section 15.

41.123 The center W 1/16 section corner of section 15.

N. 0° 27.0' W., on the N - S centerline of the NW 1/4 of section 15.

20.518 Point for the NW 1/16 section corner of section 15, at intersection with the E - W centerline of the NW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E
NW 1/16
S15
2007

Set a steel fence post alongside the aluminum post.

Corner is located 27 ft. S. of an E-W fence line.

41.036 The point for the W 1/16 section corner of sections 10 and 15.

From the point for the center N 1/16 section corner of section 15.

N. 89° 02.1' W., on the E - W centerline of the NW 1/4 of section 15.

20.075 The NW 1/16 section corner of section 15.

40.150 The N 1/16 section corner of sections 15 and 16.

The Subdivision of Section 22
T. 13 N., R. 7 E., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 22 and 27.

N. 0° 12.9' E., on the N - S centerline of section 22.

20.598 Point for the center S 1/16 section corner of section 22.

THE SUBDIVISION OF SECTION 22
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E
C
S 1/16 | S 22
C
2007

Set a steel fence post alongside the aluminum post.

41.196 Point for the center 1/4 section corner, at intersection with the E - W centerline of section 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E
C 1/4
S22
2007

Set a steel fence post alongside the aluminum post.

44.450 Burnt fence line, extends E and W.

82.509 The 1/4 section corner of sections 15 and 22.

From the 1/4 section corner of sections 22 and 23.

N. 89° 15.4' W., on the E - W centerline of section 22.

20.095 Point for the center E 1/16 section corner of section 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E
E 1/16
C ——— C
S22
2007

Set a steel fence post alongside the aluminum post.

Corner of fences bears S. 3° 20' W., 7.7 ft. distance, fences extend N and E.

40.190 The center 1/4 section corner of section 22.

60.417 Point for the center W 1/16 section corner of section 22.

THE SUBDIVISION OF SECTION 22
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E
W 1/16
C ——— C
S22
2007

Set a steel fence post alongside the aluminum post.

Corner of fences, bears NE 274 ft. distance, burnt fence line extends N and E.

80.644 The 1/4 section corner of sections 21 and 22.

From the center E 1/16 section corner of section 22.

N. 0° 20.1' E., on the N - S centerline of the NE 1/4 of section 22.

41.254 The E 1/16 section corner of sections 15 and 22.

From the point for the E 1/16 section corner of sections 22 and 27.

N. 0° 01.7' W., on the N - S centerline of the SE 1/4 of section 22.

5.134 Point for the C-S-S-SE 1/256 section corner of section 22. Not monumented.

7.570 Centerline of gravel road, extends SE and NW.

7.701 Point for the C-N-S-S-SE 1/1024 section corner of section 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

1/1024
2007

Set a steel fence post alongside the aluminum post.

8.130 Fence, extends SE and NW.

10.268 Point for the C-S-SE 1/64 section corner of section 22. Not monumented.

20.536 Point for the SE 1/16 section corner of section 22.

THE SUBDIVISION OF SECTION 22
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T13N R7E
SE 1/16
S22
2007

Set a steel fence post alongside the aluminum post.

41.073 The center E 1/16 section corner of section 22.

From the point for the S 1/16 section corner of sections 22 and 23.

N. 89° 25.9' W., on the E - W centerline of the SE 1/4 of section 22.

10.091 Point for the C-E-SE 1/64 section corner of section 22. Not monumented.

20.182 The SE 1/16 section corner of section 22.

40.364 The C-S 1/16 section corner of section 22.

From the E-E 1/64 section corner of sections 22 and 27.

N. 0° 09.0' W., on the N - S centerline of the SE 1/4 of the SE 1/4 of section 22.

1.130 Centerline of gravel road, extends SE and NW.

1.570 Fence, extends SE and NW.

2.563 Point for the C-S-S-SE-SE 1/1024 section corner of section 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

1/1024
2007

Set a steel fence post alongside aluminum post.

5.126 Point for the C-S-SE-SE 1/256 section corner of section 22. Not monumented.

10.252 Point for the SE-SE 1/64 section corner of section 22, at intersection with the E - W centerline of the SE 1/4 of the SE 1/4. Not monumented.

THE SUBDIVISION OF SECTION 22
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

20.505 The point for the C-E-SE 1/64 section corner of section 22.

From the point for the S-S 1/64 section corner of sections 22 and 23.

N. 89° 31.1' W., on the E - W centerline of the SE 1/4 of the SE 1/4 section 22.

10.112 The point for the SE-SE 1/64 section corner of section 22.

14.190 Fence, extends N and S.

15.168 Point for the C-W-SE-SE 1/256 section corner of section 22.
Not monumented.

17.696 Point for the C-W-W-SE-SE 1/1024 section corner of section 22.
Not monumented.

20.224 The point for the C-S-SE 1/64 section corner of section 22.

From the point for the W-E-E 1/256 section corner of sections 22 and 27.

N. 0° 05.3' W., on the N - S centerline of the SW 1/4 of the SE 1/4 of the SE 1/4 of section 22.

2.565 Point for the C-S-SW-SE-SE 1/1024 section corner of section 22. Not monumented.

4.560 Centerline of gravel road, extends SE and NW.

4.960 Fence, extends SE and NW.

5.130 Point for the SW-SE-SE 1/256 section corner of section 22 at intersection with the E-W centerline of the SW 1/4 of the SE 1/4 of the SE 1/4 of section 22. Not monumented.

7.695 Point for the C-N-SW-SE-SE 1/1024 section corner of section 22. Not monumented.

10.260 The point for the C-W-SE-SE 1/256 section corner of section 22.

From the point for the C-S-SE-SE 1/256 section corner of section 22.

N. 89° 33.7' W., on the E - W centerline of the SW 1/4 of the SE 1/4 of the SE 1/4 of section 22.

THE SUBDIVISION OF SECTION 22
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 2.531** Point for the C-E-SW-SE-SE 1/1024 section corner of section 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

1/1024
2007

Set a steel fence post alongside the aluminum post.
- 3.930** Fence, extends N and S.
- 5.062** The point for the SW-SE-SE 1/256 section corner of section 22.
- 5.330** Centerline of gravel road, extends SE and NW.
- 6.030** Fence, extends SE and NW.
- 7.593** Point for the C-W-SW-SE-SE 1/1024 section corner of section 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, to bedrock, with a magnet at base, with aluminum cap marked:

1/1024
2007

Set a steel fence post alongside the aluminum post.

Corner falls in pasture land.
- 10.124** The point for the C-S-S-SE 1/256 section corner of section 22.
-
- From the point for the E-W-E-E 1/1024 section corner of sections 22 and 27.

N. 0° 07.2' W., on the N - S centerline of the SE 1/4 of the SW 1/4 of the SE 1/4 of the SE 1/4 of section 22.
- 2.564** Point for the SE-SW-SE-SE 1/1024 section corner of section 22 at intersection with the E - W centerline of the SE 1/4 of the SW 1/4 of the SE 1/4 of the SE 1/4.

Set a 5/8 inch rebar, 18 inches long, 12 inches into a drill hole on solid rock, with a 1 3/4 inch aluminum cap marked:

1/1024
2007

Set a steel fence post alongside the rebar.

THE SUBDIVISION OF SECTION 22
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner falls in pasture land.

2.700 Fence, extends SE and NW.

3.200 Centerline of gravel road, extends SE and NW.

5.128 The C-E-SW-SE-SE 1/1024 section corner of section 22.

From the C-S-S-SE-SE 1/1024 section corner of section 22.

N. 89° 35.0' W., on the E - W centerline of the SE 1/4 of the SW 1/4 of the SE 1/4 of the SE 1/4 of section 22.

1.580 Centerline of gravel road, extends SE and NW.

2.310 Fence, extends SE and NW.

2.532 The SE-SW-SE-SE 1/1024 section corner of section 22.

5.064 The point for the C-S-SW-SE-SE 1/1024 section corner of section 22.

From the C-W-SW-SE-SE 1/1024 section corner of section 22.

N. 0° 03.5' W., on the N-S centerline of the NW 1/4 of the SW 1/4 of the SE 1/4 of the SE 1/4 of section 22.

0.930 Fence, extends SE and NW.

1.380 Centerline of gravel road, extends SE and NW.

2.566 Point for the NW-SW-SE-SE 1/1024 section corner of section 22 at intersection with the E - W centerline of the NW 1/4 of the SW 1/4 of the SE 1/4 of the SE 1/4 of section 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

1/1024
2007

Set a steel fence post alongside the aluminum post.

5.132 The point for the C-W-W-SE-SE 1/1024 section corner of section 22.

From the point for the C-N-SW-SE-SE 1/1024 section corner of section 22.

N. 89° 32.4' W., on the E - W centerline of the NW 1/4 of the SW 1/4 of the SE 1/4 of the SE 1/4 of section 22.

THE SUBDIVISION OF SECTION 22
T. 13 N., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 2.530** The NW-SW-SE-SE 1/1024 section corner of section 22.
- 4.350** Centerline of gravel road, extends SE and NW.
- 5.060** The C-N-S-S-SE 1/1024 section corner of section 22.
-
- From the point for the W 1/16 section corner of sections 22 and 27.
- N. 0° 16.3' E., on the N - S centerline of the SW 1/4 of section 22.
- 20.659** Point for the SW 1/16 section corner of section 22 at intersection with the E - W centerline of the SW 1/4 of section 22.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:
- T13N R7E
SW 1/16
S22
2007
- Set a steel fence post alongside the aluminum post.
- Corner falls in pasture land.
- 41.318** The C-W 1/16 section corner of section 22.
-
- From the C-S 1/16 section corner of section 22.
- N. 89° 25.9' W., on the E - W centerline of the SW 1/4 of section 22.
- 20.248** The SW 1/16 section corner of section 22.
- 40.496** The point for the S 1/16 section corner of sections 21 and 22.
-
- From the C-W 1/16 section corner of section 22.
- N. 0° 16.6' E., on the N - S centerline of the NW 1/4 of section 22.
- 41.371** The W 1/16 section corner of sections 15 and 22.
-

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Travis Hanks	Cadastral Surveyor
Glen Hatch	Cadastral Surveyor
Adrian Kurip	Survey Technician

CERTIFICATE OF SURVEY

I, **Ronald K. Baugh**, **Supervisory Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the **23rd day of July, 2007**, have **executed a dependent resurvey of a portion of the subdivisional lines, and the subdivision of sections 14, 15, and 22, in Township 13 North, Range 7 East,**

of the **Salt Lake** Meridian, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 23, 2008

Date

Ronald K. Baugh
(Supervisory Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The following field notes of the **dependent resurvey of a portion of the subdivisional lines, and the subdivision of sections 14, 15 and 22, in Township 13 North, Range 7 East,**

executed by **Ronald K. Baugh**, **Supervisory Cadastral Surveyor** having been critically examined and found correct, are hereby approved.

June 27, 2008

Date

Daniel W. Webb
(Chief Cadastral Surveyor for Utah)